

Архангельск (8182)63-90-72
 Астана (7172)727-132
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16

Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://biobase.nt-rt.ru/> || bba@nt-rt.ru

Bath / Circulator

Thermostatic Water Bath



Features:

- * Stainless steel inner chamber and upper cover.
- * Adopt new design structure, which could avoid the leakage of steam.
- * PID microprocessor controller, LED display.
- * With universal fixture for SY-1L4H and SY-1L6H.

Technical Parameters:

Model	SY-1L1H	SY-1L2H	SY-1L4H	SY-1L6H	SY-2L4H	SY-2L6H	SY-2L8H
Capacity	3L	7L	13L	20L	15L	23L	24L
Temp. Range	RT-100°C						
Temp. Fluctuation	±0.5°C						
Temp. Accuracy	±1°C						
Time Range	0-999min						
Power	300W	500W	1000W	1500W	1000W	1500W	2000W
Power Supply	AC110/220V±10%, 50/60Hz						
Internal Size(mm)	140*150*150	300*150*150	600*180*120	900*180*120	320*300*150	500*300*150	620*320*120
External Size(mm)	270*180*190	320*180*210	770*310*170	1100*310*170	340*320*210	500*320*210	750*360*160
Packing Size(mm)	320*230*220	410*220*310	820*330*250	1150*330*250	410*390*310	590*390*310	830*460*250
Net Weight(kg)	2	4	10	13	6.5	9	12
Gross Weight(kg)	3	5	11	14.5	7.5	10	13

Transparent Water Bath



Features:

- * Adopt new design structure, effectively prevent leakage of steam.
- * All made of transparent acrylic sheet, can clearly see objects that are heated.
- * High precision intelligent temperature control, digital display with high brightness.

Technical Parameters:

Model	SY-6L	SY-8L	SY-20L
Capacity	6L	8L	20L
Temp. Range	RT-100°C		
Temp. Fluctuation	0.5°C		
Temp. Accuracy	±1°C		
Tube Rack	1 pc, Height: 20mm, Diameter: 12.5mm		
Consumption	600W	1000W	1500W
Power Supply	AC110/220V±10%, 50/60Hz		
Internal Size(mm)	270*120*150	270*120*150	480*270*150
Packing Size(mm)	410*275*310	470*315*310	680*375*310
Net Weight(kg)	6	7.5	13
Gross Weight(kg)	6.8	8.5	15