

Архангельск (8182)63-90-72  
 Астана (7172)727-132  
 Астрахань (8512)99-46-04  
 Барнаул (3852)73-04-60  
 Белгород (4722)40-23-64  
 Брянск (4832)59-03-52  
 Владивосток (423)249-28-31  
 Волгоград (844)278-03-48  
 Вологда (8172)26-41-59  
 Воронеж (473)204-51-73  
 Екатеринбург (343)384-55-89  
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58  
 Иркутск (395)279-98-46  
 Казань (843)206-01-48  
 Калининград (4012)72-03-81  
 Калуга (4842)92-23-67  
 Кемерово (3842)65-04-62  
 Киров (8332)68-02-04  
 Краснодар (861)203-40-90  
 Красноярск (391)204-63-61  
 Курск (4712)77-13-04  
 Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
 Москва (495)268-04-70  
 Мурманск (8152)59-64-93  
 Набережные Челны (8552)20-53-41  
 Нижний Новгород (831)429-08-12  
 Новокузнецк (3843)20-46-81  
 Новосибирск (383)227-86-73  
 Омск (3812)21-46-40  
 Орел (4862)44-53-42  
 Оренбург (3532)37-68-04  
 Пенза (8412)22-31-16

Пермь (342)205-81-47  
 Ростов-на-Дону (863)308-18-15  
 Рязань (4912)46-61-64  
 Самара (846)206-03-16  
 Санкт-Петербург (812)309-46-40  
 Саратов (845)249-38-78  
 Севастополь (8692)22-31-93  
 Симферополь (3652)67-13-56  
 Смоленск (4812)29-41-54  
 Сочи (862)225-72-31  
 Ставрополь (8652)20-65-13

Сургут (3462)77-98-35  
 Тверь (4822)63-31-35  
 Томск (3822)98-41-53  
 Тула (4872)74-02-29  
 Тюмень (3452)66-21-18  
 Ульяновск (8422)24-23-59  
 Уфа (347)229-48-12  
 Хабаровск (4212)92-98-04  
 Челябинск (351)202-03-61  
 Череповец (8202)49-02-64  
 Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://biobase.nt-rt.ru/> || [bba@nt-rt.ru](mailto:bba@nt-rt.ru)

## BA-B Series Electronic Analytical Balance (External Calibration)

### Features:

- \* Humanized design, novel design and five-side full-transparent windshield.
- \* A new-generation electromagnetic balance weighing sensor guarantees high precision.
- \* Application programs such as automatic fault detection, four-point linear calibration and over-load protection.
- \* Ultra-large LCD display brings clearer and more comfortable visual sense to operate.



### Functions:

- \* Multiple functions guarantee easy and reliable operation, including auto-counting, unit conversion (metric carat, gold ounce, etc.), stability, full-scale faring, zero-memory, etc.
- \* Built-in RS232C output interface guarantees direct connection to external equipment such as computer and printer.
- \* Built-in lower weighing hook guarantees convenient use.

Power Supply: AC110/220V±10%, 50/60Hz; Power Cord, no battery.

### Technical Parameters:

Model	Capacity	Readability	Scale Size	N.W.	External Size	Package Size	Work Space Height	Calibration
BA504B	0~50g	0.1mg	Φ80mm	6.8kg	350*215*340mm	480*375*515mm	240mm	External Cal
BA604B	0~60g							
BA1004B	0~100g							
BA1104B	0~110g							
BA1204B	0~120g							
BA1604B	0~160g							
BA2004B	0~200g							
BA2204B	0~220g							
BA2104B	0~210g							
BA2104S	0~60g 60~210g							

### Standard Accessory:

Balance body, adapter, weight, windshield, cleaning cloth, tweezers and brush.

## BP-B/P Series Electronic Precision Balance

### Features:

- \* Humanized design, novel design and five-side full-transparent windshield.
- \* A new-generation electromagnetic balance weighing sensor guarantee high precision.
- \* Application programs such as automatic fault detection, four-point linear calibration and over-load protection.
- \* Ultra-large LCD display brings clearer and more comfortable visual sense to operate.
- \* Built-in lower weighing hook guarantees convenient use.



### Functions:

- \* Multiple functions guarantee easy and reliable operation, including auto-counting, unit conversion (metric carat, gold ounce, etc.), stability, full-scale faring, zero-memory, etc.
- \* Built-in RS232C output interface guarantees direct connection to external equipment such as computer and printer.
- \* Built-in lower weighing hook guarantees convenient use.

Power Supply: AC110/220V±10%, 50/60Hz; Power Cord, no battery.

### Technical Parameters:

Model	Capacity	Readability	Scale Size	N.W.	External Size	Package Size	Work Space Height	Calibration		
BP1003B	0~100g	1mg	Φ80mm	6.8kg	350*215*340mm	480*375*515mm	240mm	External Cal		
BP1203B	0~120g									
BP2003B	0~200g									
BP3003B	0~300g									
BP4103B	0~410g									
BP5003B	0~500g		Φ110mm	6kg						
BP10003	0~1000g									
BP1003P	0~100g								Φ80mm	6.8kg
BP2003P	0~200g									

### Standard Accessory:

Balance body, adapter, weight, windshield, cleaning cloth, tweezers and brush.